



AL-P401W

Amcrest Link 4MP Wi-Fi Pan/Tilt Indoor Security Camera

Technical Specifications

Model	AL-P401W
Camera	
Image Sensor	1/3" CMOS
Resolution	4MP (2560 x 1440)
ROM	8MB
RAM	64MB
Min. Illumination	3Lux (IR off), 1Lux (IR on)
Night Vision	4 IR LEDs (Up to 30ft)
IR On/Off Control	Auto/Manual
Viewing Angle	82°
Pan/Tilt	345°Pan & -20 ~ 16°Tilt
Lens Type	Fixed-focal
Mount Type	M12
Focal Length	3.6mm
Aperture	F2.0
Camera Features	
Motion Detection	Supported
Human Detection	Supported
Human Tracking	Supported
2-Way Audio	Built-in Mic and Speaker
Active Deterrents	Built-in Siren (max 95±3dB)
Video	
Compression	H.264
Streaming Capability	Mainstream (2560 x 1440) @15 fps; sub stream (640 x 480 @15 fps)
Day/Night	Auto (ICR)/Color/B/W
BLC	Supported
WDR	DWDR
White Balance	Auto
Gain Control	Auto
Noise Reduction	3D NR
Image Rotation	0°/180°
Image Flip	Supported
Auxiliary Interface	
Audio Interface	Built-in Mic & Speaker (Two-Way Audio)
Audio Compression	PT_711A/711U PT_726 PT_ADPCM
Auxiliary Interface	Micro SD Card Slot (up to 128GB) Reset Button

Network	
Ethernet	Not Supported
Connection	Bluetooth
Wi-Fi	Wi-Fi: IEEE 802.11b/g/n, 50m Open Field
Wi-Fi Frequency Range	Dual Band (2.4GHz or 5GHz)
User/Host	20 (Total bandwidth: 24M)
Edge Storage	MicroSD card (Max. 128GB), Amcrest Link Cloud
Management Software	Amcrest Link app, Amcrest Link Cloud
Smart Phone	IOS, Android
General	
Power Supply	DC 5V (USB Type-C)
Power Consumption	2.95W
Atmospheric Pressure	86kpa-106kpa
Operating Temperatures	14°F ~ 113°F
Operating Humidity	≤95%
Casing	Plastic
Dimensions (L x W x H)	3.15" x 3.15" x 4.45"
Weight	0.37 lbs.