

RLC-422-Refurbished-IP-Camera-Specifications

	Model	RLC-422 (Refurbished)
Video	Video Resolution	Default: 5.0 Megapixels
	Video Format	H.264
	Angle of View	Horizontal: 90°~31°, vertical: 67°~24°
	Day/Night Mode	Auto switchover
	Min. Illumination	0 Lux (with IR Illuminator)
	Infrared Night Vision	30 meters (100ft)
	Optical Zoom	4X
Power	POE	IEEE 802.3af, 48V active
	DC Power	DC 12.0V=1A, <10W
Interface	Power	DC power port
	System	Reset button
	Ethernet	One 10M/100Mbps; RJ45
Software Features	Frame Rate	Up to 25fps
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Alarm	Motion detection
	Record Mode	Motion recording
	Max. User Access	20 users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams).
Working Environment	Temperature	Operating temperature: -10°C ~ +55°C (14°F~131°F)
	Humidity	Operating humidity: 20% ~ 85%
Size & Weight	Dimensions	Φ133x100mm
	Weight	720g
Warranty	Limited Warranty	1-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .