

RLK8-824D4-A-NVR-Kit-NVR-Specifications		
	Model	RLN8-410
<b>Hardware</b>	Hardware	V2
<b>Video/Audio Input</b>	IP Video Input	PoE IP camera x 8
	Audio Input	Cameras with built-in mic
<b>Video/Audio Output</b>	Video Output	VGA, HDMI
	Display Resolution	<b>HDMI:</b> 4096*3072, 3840*2160, 1920*1080, 1440*900, 1280*1024, 1280*720, 1024*768
		<b>VGA:</b> 1920*1080, 1440*900, 1280*1024, 1280*800, 1280*720, 1024*768
Audio output	1-channel, RCA	
<b>Decoding</b>	Video Format	H.264, H.265
	Live View/Playback Resolution	4096*3072/3840*2160/2560*1920/2560*1440/2048*1536/2304*1296/1080p/720p
	Synchronous Playback	Up to 4 channels
<b>HDD</b>	SATA	1 x SATA interface (1 x Seagate 2TB HDD included)
	External HDD	1 eSATA interface for HDD
	Capacity	Up to 12TB (Max. 6TB capacity for each HDD)
<b>External Interface</b>	USB Interface	2 x USB 2.0
	Network Interface	1, RJ-45 10/100 Mbps self-adaptive Ethernet interface for LAN/WAN 8, RJ-45 10/100 Mbps self-adaptive PoE Ethernet interface for IP camera
<b>PoE</b>	Max. Power Per Port	25W
	Supported Standard	IEEE 802.3af/at
<b>Network</b>	Network Protocols	HTTP, TCP/IP, UDP, DHCP, P2P, UPNP, RTSP, SMTP, SSL/TLS, DNS, DDNS, NTP, FTP
	Browsers Supported	IE, Edge, Firefox, Chrome, Safari
	OS Supported	PC: Windows, Mac OS; SmartPhone: iOS, Android
	Max. User Access	20 users (1 admin account & 19 user accounts); supports up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
<b>General</b>	Power Supply	DC 48V/1.875-2.5A
	Power Consumption	<10W (without HDD&PoE)
	Working Environment	Temperature: -10°C~+45°C (14°F~113°F); humidity: 10%~90%
	Dimensions	260 x 41 x 230mm
	Weight	1.4kg
<b>Warranty</b>	Limited Warranty	2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a> .