

Reolink TrackMix LTE (C)

4K 4G Dual-Lens Battery Security Camera with Auto-Zoom, Dual View and Smart Detection

- 4K 8MP Ultra HD
- Dual View, Dual Tracking
- 4G LTE Network
- Person/Vehicle/Animal Detection



Specifications

Video & Audio	
Image Sensor	1/3"CMOS Sensor
Video Resolution	Up to 3840 x 2160 (8.0 megapixels) at 15 frames/sec
Lens	f=2.8mm@F=1.6, f=8mm@F=1.6
VideofORMAT	H.264, H.265
Field of View	Horizontal: 108.4°-38° Vertical: 57.3°-21.2°
Zoom Mode	6X hybrid zoom
Day & Night	IR-cut filter with auto-switching
Infrared Night Vision	Up to 30 meters (100ft) (LED: 2pcs/940nm)
Color Night Vision	Spotlight: 1pcs/6500K/450 lumens
Audio	Two-way audio

Power	
Battery	7.2V 5100mAh rechargeable battery (Battery life varies, based on settings, usage & temperature); 36.72Wh(Power capacity)
Solar	Reolink Solar Panel 2
DC Power	5V/2A
Interface	
Power	USB Type-C port
System	Reset button
Storage	microSD card slot (max. 128GB)
Network	Nano SIM card slot
Audio	Built-in microphone and speaker
Pan & Tilt	
Pan &Tilt	Pan: 355°, Tilt: 0°~90°; (Speed can be set)
Preset	32
Auto Tracking	Support
3G/4G Bandwidth	
 Frequency Bands	Europe version: LTE FDD: B1/B3/B7/B8/ B20/B28A WCDMA: B1/B8 USA version: LTE FDD: B2/B4/B5/B12/ B13/B14/B66/B71 WCDMA: B2/B4/B5 Australia version: LTE FDD: B1/B3/B5/ B7/B8/B28 LTE-TDD: B40 WCDMA: B1/ B5/B8
Transmission Data	LTE FDD: Max. 10Mbps (DL), Max. 5Mbps (UL) LTE TDD: Max. 8.96Mbps (DL), Max. 3.1Mbps (UL) HSPA+: Max. 42Mbps (DL), Max. 5.76Mbps (UL) UMTS: Max. 384Kbps (DL), Max. 384Kbps (UL)
Software Features	
Frame Rate	

	Mainstream: 10fps - 15fps Substream: 10fps - 15fps
Code Rate	Mainstream: 1024Kbps - 4096Kbps Substream: 64Kbps - 512Kbps
OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Smart Alarm	PIR detection/person detection/ vehicle detection/pet detection
Record Mode	Motion-triggered recording
Protocols & Standards	SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P
MaximumUser Access	Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
Work with	Google Assistant, Reolink Cloud
Working Environment	
Operating Temperature	-10°C~+55°C (14°F~131°F)
Operating Humidity	20% ~ 85%
Weatherproof	IP65
Size & Weight	
Dimensions	228.2*147*129mm
Weight	1.4kg
Warranty	
Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .

Gallery & Specs



1. Spotlight
2. Infrared LED
3. Lens
4. Mic
5. Daylight Sensor
6. PIR Sensor



1. microSD Card Slot



1. SIM Card Slot