

TAPO OTHER GUIDE

OpticLink Pro - Automated Device Technical Manual & Integration Guide

1. HARDWARE SPECIFICATIONS

Brand Name: Tapo

Supported Models: Other, TP-Link, TP-Link 15C200, TP-Link 3.20, TP-Link 310C, TP-Li...

Device Type: FFMPEG

Compression Formats: H.264 / H.265 (High Efficiency)

Audio Type: Supported

2. CONNECTION & PROTOCOL REFERENCE

Supported Connection Protocol: rtsp://

Authoritative RTSP Stream Path: /stream1

Sub Stream Stream Path: rtsp://[IP_ADDRESS]:554/stream2

ONVIF Service Port: 8899 / 80

3. STREAM & PERFORMANCE SETTINGS

Maximum Supported Stream Frame Rate: 25 FPS

Recommended Stream Bitrate: 2048 - 4096 Kbps

Resolution Settings: Fully Adjustable via Official App

Sub Stream Frame Rate: 15 FPS

4. INTEGRATION & QUICK SETUP GUIDE

1. Enable ONVIF/RTSP functionality within the official Tapo application.
2. Establish a static IP address or DHCP reservation for the camera.
3. Input the primary stream RTSP URL directly into your OpticLink dashboard.
4. Configure motion zones and audio detection parameters to maximize utility.